

Highly resilient soundproofing sealant

QuietSeal is ideal for use with QuietRock, QuietWood, QuietPutty and QuietGlue in construction projects, as it is specifically designed for sound isolation and for interior use between joints. Use to seal around perimeters and openings in partitions. QuietSeal is highly resilient, withstanding any amount of movement normally encountered in partitions. It can be applied as a sealant to all clean concrete, gypsum, plaster, steel, wood and aluminum surfaces without priming.

QuietSeal Benefits

- Excellent for use with QuietRock, QuietWood, QuietPutty and QuietGlue in construction projects
- High quality sound isolating sealant/caulk
- Maintains high STC ratings
- Remains permanently soft and tacky
- Convenient 29 oz and 10.5 oz tubes
- Environmentally friendly, lab tested

Product Specifications

Model:	QuietSeal 350
Color:	Yellow (ASTM D2452-75)
Solid content:	91 wt% (ASTM C681-73)
Weight:	14.1 lbs/gallon (ASTM D1457-60)
Volume shrinkage:	< 18% (ASTM D2453-75)
Layer thickness:	1/16"
Drying time:	Remains soft
Engageability:	-10° F
Threshold:	TLV 200 ppm
Storage temp:	40° - 100° F (Do not freeze)
Coverage:	38 lineal feet per 29.5 oz tube at 3/8" bead
Flexibility:	No cracking or loss of adhesion at -60°F bent 180° over 1/4" mandrel (ASTM C711-72)
Service temp:	-40°F to + 240°F
Weatherability:	After 1,000 hours in weatherometer, no cracking, bleeding or loss of rubber characteristics (ASTM D750-68)
Safety:	Wet flammability (ASTM D93-80) 125°F Dry flammability - combustible (450°F)
Specifications:	Canadian specification CGSB 19-GP-21M. American Federal Specification TT-C-1796A, Type 1, Class A
Shelf life:	One year in sealed container
Clean up:	Paint thinner or lacquer thinner



Product Application

QuietSeal should be applied between track or runner, walls, floors and ceilings, as well as between panel edges and contact surfaces. Use a full 3/8" bead into joints before placing the next panel. The number of beads required will vary from one to two in most applications depending on the size of the potential airgap. Special problem areas may require a premolded, loose-cell filler or additional sealant between track and drywall at top and bottom edges, according to design specifications.

QuietSeal is designed strictly for interior use between joints. It should not be applied at the sight-line, where dirt pick-up is likely, except where molding or joint taping will conceal it. A non-skinning sealant such as QuietSeal cannot be painted over. QuietSeal is easily removed from unwanted surfaces with any paint thinner.