



QuietTile Application Instructions

Packaging: 1-gallon and 5-gallon pails

Shelf life: 12 months, when stored in the original unopened packaging, in a dry place at <86°F (30°C) and 50% relative humidity.

Coverage: One gallon of QuietTile will cover approximately 40–80 ft² of tiling when using a 5/32" V-notched trowel. Coverage will vary depending on substrate conditions and application technique.

Drying time: Approximately 72 hours, at 73°F (23°C) and 50% relative humidity. Dries by moisture evaporation, so allow longer for dense tiles/substrates, humid climates and low temperatures.

Surface preparation: Surfaces must be consistently flat and firmly fixed. Clean off dust, oil, grease and all loose contaminating materials. Ensure surfaces are dry before tiling, with no residue or permanent damp. For instructions on preparation of specific surfaces, refer to packaging.

Mixing: No mixing required.

Application: Before fixing tiles ensure the back of the tiles are free from dust. Apply QuietTile at a bed thickness between 0.040" and 0.120" (1mm to 3mm). As a guide, use a 5/32" V-notched trowel to spread the adhesive, ensuring it does not skin prior to bedding the tiles. Press and slide the tile at right angles to the notch pattern to ensure 100% coverage on the back of the tile. Lift a tile from time to time and check that there are no voids beneath the tile. Any surplus adhesive should be removed from the surface of the tile and joints before the adhesive sets. Allow to fully dry before grouting. For detailed instructions, refer to label.

Precautions

- Do not use QuietTile for continuous immersion applications (swimming pools, water tanks).
- Do not use to fix green marble or moisture-sensitive natural stone.
- Do not use for non-porous tiles over non-porous substrates (e.g. monocuttura or dense tiles over waterproofing membrane) or shower hobs due to unsatisfactory drying times.

Quiet Solution
1250 Elko Drive
Sunnyvale, CA 94089
www.QuietSolution.com